



TECHNICAL INFORMATION: TAJ Med Floor Homogeneous Sheet Flooring

Product Description: TAJ Med Floor is a high performance homogeneous through color heat welded commercial sheet vinyl product with a no wax, no buff UV cured urethane coating.

Classification: F-1913

Overall Thickness: 2mm (0.080 inches)

Wear Layer Thickness: 2mm (0.080 inches)

Roll Size: 6' x 59", 47.84 square yards per roll

Wear Layer: Through Color Construction

Finish: Protech UV cured urethane coating technology which eliminates the need for floor finishes and improves hygiene and chemical resistance.

Warranty: 15 Year Commercial Warranty

Maintenance: Requires no wax, no stripping, no buffing, nor the use of toxic chemical for routine maintenance.

Test	Result
Static Load Limit: ASTM F970 modified	Passes at 1100psi
Chemical and Stain Resistance: ASTM F925	Excellent
Coefficient of Friction: ASTM C1028-89	Wet: .79 Dry: .71
VOC Emissions	Negligible
Flame Spread: ASTM E648	>.45, Class 1
Smoke Density: ASTM E662	<450

Installation: Inspect subfloor surfaces carefully to determine acceptability per TAJ installation instructions. Approved adhesives, TAJ Eco Bond Spray Adhesive, TAJ 585 Adhesive, 2 Part Urethane or Epoxy Hard Set Adhesive such as Mapei G-15, G-19, or G-21.

LEED: Low emitting flooring IEQ4.3, Low emitting adhesives IEQ4.1

Indoor Air Quality: CHPS 1350 Certified, FloorScore Certified

Plant Certifications: ISO 14001, ISO 9001

Trade Agreements Act (TAA) Compliant