



MATERIAL SAFETY DATA SHEET

Resilient Sheet Vinyl Flooring

MSDS DATE: 2/1/16

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Resilient Sheet Vinyl Flooring

COMPANY INFORMATION: TAJ Flooring, Inc.
ADDRESS: 740 Church Road
Elgin, IL 60123

EMERGENCY PHONE: 847-690-9930
CHEMTREC PHONE: 847-690-9930 x160
OTHER CALLS: 888-652-2111
FAX PHONE: 847-690-9331

CHEMICAL NAME: Resilient Sheet Vinyl Flooring

PRODUCT USE: Floor Covering
PREPARED BY: TAJ Flooring Inc. Technical Services

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

None per OSHA Standard 29 CFR 1910.1200 and SARA Title III, Section 313

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:
Form: Sheet vinyl floor covering
Color: Varies
Odor: No appreciable odor

WARNING STATEMENTS:
None

POTENTIAL HEALTH EFFECTS
Primary Routes of Exposure: N/A
EYES: N/A
SKIN: N/A
INGESTION: N/A
INHALATION: N/A

ACUTE HEALTH HAZARDS: None known
CHRONIC HEALTH HAZARDS: None known
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: N/A

OTHER: This product is an article or building product and is relatively non-toxic, presenting no known hazard to people, except as noted under thermal decomposition by-products

SECTION 3 NOTES: Refer to section 11 for toxicology information.

SECTION 4: FIRST AID MEASURES

EYES: Flush with cool water, like any non-hazardous solid
SKIN: If skin is irritated from handling product (transitory mechanical dermatitis), wash thoroughly with soap and water. Seek medical attention if condition persists.
INGESTION: Seek medical attention if a considerable amount has been swallowed
INHALATION: None expected from product. Remove to fresh air and seek medical assistance if adverse reaction to adhesive should occur.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: None

MATERIAL SAFETY DATA SHEET

Resilient Sheet Vinyl Flooring

MSDS DATE: 2/1/16

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: N/A
(% BY VOLUME) LOWER: N/A

FLASH POINT: N/A

AUTOIGNITION TEMPERATURE: N/A

NFPA HAZARD CLASSIFICATION: N/A

EXTINGUISHING MEDIA: On its own, product is difficult to ignite. Use water spray or other appropriate media for surrounding fire

SPECIAL FIRE FIGHTING PROCEDURES: Protect fire fighters from toxic products of combustion by wearing self-contained breathing apparatus and full protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None

HAZARDOUS DECOMPOSITION PRODUCTS: Protect self from melted product and combustion products.

SECTION 5 NOTES: ASTM E-648 CRF value greater than 0.45 w/square cm; material is considered to be self-extinguishing.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: None, This is a non-hazardous product.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Consult TAJ installation instructions for information on handling and storage of this non-hazardous product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Install in well ventilated area

RESPIRATORY PROTECTION: Normally not required

EYE PROTECTION: Normally not required

SKIN PROTECTION: Normally not required

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Normally not required

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Solid, flooring tiles

ODOR: No appreciable odor

PHYSICAL STATE: Solid, flooring tiles

pH: N/A

BOILING POINT: N/A

MELTING POINT: N/A

FREEZING POINT: N/A

VAPOR PRESSURE (mmHg): N/A

VAPOR DENSITY (AIR = 1): N/A

SPECIFIC GRAVITY (H₂O = 1): 1.30 – 1.60

EVAPORATION RATE: N/A

SOLUBILITY IN WATER: N/A

SECTION 10: STABILITY AND REACTIVITY

CONDITIONS TO AVOID (STABILITY): Stable

INCOMPATIBILITY (MATERIAL TO AVOID): Stable

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: Thermal decomposition in the presence of air may yield hydrogen chloride gas, carbon dioxide and carbon monoxide.

HAZARDOUS POLYMERIZATION: Will not occur



MATERIAL SAFETY DATA SHEET

Resilient Sheet Vinyl Flooring

MSDS DATE: 2/1/16

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Non-toxic

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No ecological impact study information is available on this product.

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Disposal should be done in accordance with all local, state and federal (40 CFR Part 261) regulations. Be aware that state and local requirements differ widely depending on location and may in many cases be different from federal regulation.

RCRA HAZARD CLASS: N/A

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: Not regulated

HAZARD CLASS: Not regulated

ID NUMBER: N/A

SECTION 14 NOTES: The information in this section is for example only. Please apply the appropriate regulations to properly classify your shipment for transport.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): N/A

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): N/A

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): N/A

311/312 HAZARD CATEGORIES: N/A

SECTION 16: OTHER INFORMATION

OTHER INFORMATION: This material is a finished floor covering product. TAJ Flooring provides a Product Safety Data Sheet on all finished floor covering products.

Product Safety Data Sheets (PSDS) are provided for finished floor covering products based on the "article exemption" found in 29 CFR 1910.1200 (b) (6) (v). An article is defined as: "a manufactured item other than a fluid or particle: (i) which is formed to a specific shape or design during manufacture; (ii) which has an end use function(s) dependent in whole or in part upon its shape or design during end use; and (iii) which under normal conditions of use, does not release more than very small quantities, e.g. minute or trace amounts of a hazardous chemical and does not pose a physical hazard or health risk to employees."

Material Safety Data Sheets for all sundry products (adhesives, maintenance products, etc.) can be obtained by contacting TAJ Flooring customer service at 888-652-2111.

Because most floor installations require adhesives, it is recommended that the user review the manufacture's recommendations for adhesive spread rate, open time, proper ventilation, safe installation practices, etc. prior to and during installation.

DISCLAIMER: Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct as of the date of hereof, the company makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving same will make their own determination as to its suitability for their purposes prior to use. In no event will the company be responsible for damages of any nature whatsoever resulting from the use of or reliance upon this information. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OF ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO INFORMATION OR THE PRODUCT TO WHICH THE INFORMATION REFERS.