

MODULAR Flooring Adhesive

TECH DATA

PRODUCT CHARACTERISTICS

TAJ Modular Flooring Adhesive is a versatile spray adhesive naturally suited for adhering Vinyl Composition Tile (VCT) in commercial and residential applications.

It uses 80% less adhesive compared to trowel applied epoxy and bucket adhesive. Its instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads. Also, it is a non-toxic, 0.020 g/ml VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- Uses 80% less adhesive
- Allows all traffic immediately
- 0.020 g/ml VOC content
- Non-toxic, water-based adhesive
- No need to shut down HVAC
- Easy water cleanup while adhesive is still wet
- Non-flammable
- High moisture and pH resistant
- No offensive odors

COVERAGE

For approved VCT flooring in an upside down aerosol can.

170-200 sq ft per can

SUITABLE SUBSTRATES

TAJ Modular Flooring Adhesive bonds approved VCT flooring to the following properly prepared, smooth, flat, dust-free substrates:

- Concrete
- Underlayment grade plywood
- Metal
- Fiberglass
- Existing VCT

TECHNICAL CHARACTERISTICS

- Provides immediate shear strength after installation allowing instant access to finished floor.
- Solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.
- Uses non-ozone depleting HFC propellant.
- Withstands 8 lbs. of vapor emissions, 90% RH and 11 pH.



*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	2 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 8 lbs/1,000 sq ft or 90% RH/11pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



740 Church Road, Elgin, IL 60123
P: 888.652.2111 or 847.690.9930 | F: 847-690-9931

REV: Release
DATE: 9.6.16