

TECHNICAL SPECIFICATION

TAJ Majestic Phthalate Free Sheet Flooring




Majestic Phthalate Free Sheet Flooring is a high-performance phthalate free fiberglass reinforced low maintenance antimicrobial heterogeneous commercial sheet vinyl product. Majestic vinyl sheet is built with a Protech Plus® ceramic bead infused UV cured polyurethane finish which has 2x the scratch resistance of standard urethane coatings. Protech Plus® eliminates the need for floor finishes and improves hygiene with an EPA approved anti-bacterial treatment which effectively removes 99.9% of surface bacteria.



Table with 4 columns: Product Details, Overall Product Thickness, Warranty, Wear Layer Thickness, Dimensions, Wear Layer, and SQ YD per Roll.

Test Results Data: The following data is supported by independent testing companies. Copies of test results are available upon request.

Table with 2 columns: TEST and RESULT. Lists various ASTM and industry standards such as ASTM F1303, ASTM E648, and LEED.



Installation: Inspect subfloor surfaces carefully to determine acceptability. All TAJ flooring products must be installed under proper site conditions. Prior to installation, reviewing our Installation Instructions guide is strongly advised. Approved adhesives:

- TAJ Eco Bond Spray Adhesive: Maximum 8.0 lbs. MVER (Moisture Vapor Emission Rate) per 1,000 sf per 24 hours as tested by ASTM F1869 or maximum RH (Relative Humidity) of 95% as tested by ASTM F2170. Test pH of concrete – pH should be 11 or less as tested by ASTM F710.
• TAJ-1095 Adhesive: Maximum 10.0 lbs. MVER per 1,000 sf per 24 hours as tested by ASTM F1869 or maximum RH of 95% as tested by ASTM F2170. Test pH of concrete – pH should be from 5-12.
• TAJ U100 High Moisture Capable Wet Set Adhesive: Appropriate for up to 100% RH, pH between 5-14, no moisture testing required.

Protection: Although not required, the use of high-quality floor finishes will further protect the floor in heavy traffic areas. Chair and table legs should be capped with the proper floor protection glides.

TECHNICAL SPECIFICATION

TAJ Majestic Phthalate Free Sheet Flooring 



Maintenance: Use of quality floor finishes is not required. If a flooring finish is desired, the use of a floor finish will further protect the floor in heavy traffic areas. Chairs and table legs should be capped with metal swivel glides. See detailed Maintenance Instructions.

Plant Certifications: ISO14001, ISO9000



Scan or [click here](#) to view this collection online and to order samples, or to contact our team for more information and assistance.

