

TECHNICAL SPECIFICATION

TAJ Lockdown Interlocking Tile



Lockdown Interlocking Tile is a fiberglass reinforced heterogeneous modular floor tile with a unique puzzle edge interlocking system. TAJ Lockdown is manufactured with high molecular weight polymerized wear layer which is supported by high strength vinyl backing. The modular tile is sealed with Protech Plus® UV cured, ceramic bead infused polyurethane finish which enhances ease of maintenance and provides antimicrobial performance through Non-Nano Silver EPA approved technology. This product is Trade Agreements Act (TAA) compliant.



Table with 2 columns: Product Details and Specifications. Rows include Overall Product Thickness (5.0MM), Dimensions (Tile: 18" x 18"), Wear Layer (0.5MM (20mil)), Pieces per Carton (18" x 18": 10 tiles), Warranty (20 Year Commercial), and SQ FT per Carton (18" x 18": 22.50 sq ft).

Test Results Data: The following data is supported by independent testing companies. Copies of test results are available upon request.

Table with 2 columns: TEST and RESULT. Rows include ASTM F1700 Product Classification (Class III, Type B (embossed)), ASTM E648 Fire Resistance (Class 1 > 0.45), ASTM E662 Smoke Density (< 450, Flaming/Non-Flaming), ASTM F970 Static Load (1000 psi), ASTM C1028-89 Slip Resistance (> 0.6 per ADA), ASTM E492 Impact Sound Conduction (IIC 57), ASTM E90 Airborne Sound Transmission (STC 62), Chemical & Stain Resistance (Excellent), VOC Emission (Negligible), FloorScore® Certified (Yes), LEED (MR4, IEQ4.1, IEQ4.3), and Recyclable Content (42% post-consumer, 28% pre-consumer).



Scan or click here to access technical information including full warranty, installation and maintenance guides, certifications and more.

Installation: Inspect subfloor surfaces carefully to determine acceptability. All TAJ flooring products must be installed under proper site conditions. Prior to installation, reviewing our Installation Instructions guide is strongly advised.

Approved Adhesives: For most applications, Lockdown's interlocking edge allows for installations where adhesive is not required. Contact TAJ if adhesive suggestions are desired.

Protection: Although not required, the use of high-quality floor finishes will further protect the floor in heavy traffic areas. Chair and table legs should be capped with the proper floor protection glides.

TECHNICAL SPECIFICATION

TAJ Lockdown Interlocking Tile 



Maintenance: Use of quality floor finishes is not required. If a flooring finish is desired, the use of a floor finish will further protect the floor in heavy traffic areas. Chairs and table legs should be capped with metal swivel glides. See detailed Maintenance Instructions.

Plant Certifications: ISO14001, ISO9000



Scan or [click here](#) to view this collection online and to order samples, or to contact our team for more information and assistance.

