

Eco Bond LVT

TECH DATA

PRODUCT CHARACTERISTICS

TAJ Eco Bond LVT spray adhesive is a versatile spray adhesive naturally suited for adhering approved Luxury Vinyl Tile, Luxury Vinyl Plank and Carpet Tile in commercial and residential applications.

It uses 80% less adhesive compared to trowel-applied epoxy and bucket adhesive. Its instant shear strength allows for all traffic without any adhesive indentation, displacement, or movement associated with heavy weight-bearing loads.

It is a non-toxic, 0.020 g/ml VOC product that allows occupation of space as soon as installation is complete.

ADVANTAGES

- **Uses 80% less adhesive**
- **Allows all traffic immediately**
- **0.020 g/ml VOC content**
- **Non-toxic, water-based adhesive**
- **No need to shut down HVAC**
- **Easy water cleanup while adhesive is still wet**
- **Non-flammable**
- **High moisture and pH resistant**
- **No offensive odors**

COVERAGE

For approved LVT, LVP and Carpet Tile in an upside down aerosol can.

150-185 sq ft per can

SUITABLE SUBSTRATES

TAJ Eco Bond LVT spray adhesive bonds approved LVT, LVP and Carpet Tile to the following properly prepared, smooth, flat, dust-free substrates:

- **Concrete**
- **Underlayment grade plywood**
- **Metal**
- **Fiberglass**
- **Existing VCT**

TECHNICAL CHARACTERISTICS

- Provides immediate shear strength after installation allowing instant access to finished floor.
- Solvent free, emits no harmful fumes, and contains 0.020 g/ml VOC (Volatile Organic Compounds) in content, according to EPA Test Method 8260B.
- Uses non-ozone depleting HFC propellant.
- Withstands 8 lbs. of vapor emissions, 90% RH and 11 pH.



*According to EPA document: "National Volatile Organic Compound Emission Standards For Consumer Products" for aerosol adhesives.

CHEMICAL TYPE	Water-based acrylic blend
APPEARANCE	Milky white frost bubbles
ODOR	Sweet mild odor
FLASH POINT	Will not burn
NFPA 704 FLAMMABILITY RATING	0 (Non-flammable)
SHELF LIFE	3 years, if unopened
OPEN TIME	4 hours
DRY TIME	Once adhesive is dry to touch (10-20 minutes)
VOC CONTENT	0.020 g/ml calculated per EPA Test Method 8260B
FOOT TRAFFIC ALLOWANCE	Immediately
HEAVY MACHINERY ALLOWANCE	Immediately
RESISTANCE TO MOISTURE	Excellent: 8 lbs/1,000 sq ft or 90% RH/11pH
UNDERFLOOR HEATING SYSTEMS	Yes
STORAGE	Do not subject to freezing temperatures



740 Church Road, Elgin, IL 60123
P: 888.652.2111 or 847.690.9930 | F: 847-690-9931

REV: Release
DATE: 9.6.16

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name : TAJ Eco Bond LVT

Product code : Not available

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Adhesive

1.3. Details of the supplier of the safety data sheet

TAJ Flooring, Inc.
740 Church Road
Elgin, IL 60123 - USA

T 847-690-9930

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1 (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Gases under pressure – Liquefied gas
Carcinogenicity 2

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS04

GHS08

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : Contains gas under pressure; may explode if heated. Suspected of causing cancer.

Precautionary statements (GHS-US) : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. If exposed or concerned: Get medical advice/attention. Store locked up. Protect from sunlight. Store in a well-ventilated place. Dispose of contents and container in accordance with all local, regional, national and international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

None

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
1,1-Difluoroethane	(CAS No) 75-37-6	10 - 30	Flam. Gas 1 Liquefied gas
Vinyl acetate	(CAS No) 108-05-4	0.1 - 1	Flam. Liq. 2 Acute Tox. 4 (Inhalation) Carc. 2 STOT SE 3

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

TAJ Eco Bond LVT

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
- First-aid measures after skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
- First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
- First-aid measures after ingestion : If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory tract irritation.
- Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
- Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
- Symptoms/injuries after ingestion : Not a normal route of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Powder, water spray, foam, carbon dioxide.
- Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon.

5.3. Advice for firefighters

- Firefighting instructions : Cool closed containers exposed to fire with water.
- Protection during firefighting : Containers may explode when heated. Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Eliminate sources of ignition. Ruptured cylinders may rocket.

6.2. Methods and material for containment and cleaning up

- For containment : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).
- Methods for cleaning up : Scoop up material and place in a disposal container. Provide ventilation.

6.3. Reference to other sections

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Keep away from sources of ignition. - No smoking. Avoid contact with skin and eyes. Avoid breathing vapor or mist. Use only in well-ventilated areas. When using do not eat, drink or smoke. Pressurized container: Do not pierce or burn, even after use.
- Hygiene measures : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep locked up and out of reach of children. Store away from direct sunlight or other heat sources. Do not store at temperatures above 49 °C / 120 °F. Keep from freezing. Store in a well-ventilated place.

7.3. Specific end use(s)

Not available.

TAJ Eco Bond LVT

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

1,1-Difluoroethane (75-37-6)		
USA ACGIH	ACGIH TWA (ppm)	Not applicable
USA ACGIH	ACGIH STEL (ppm)	Not applicable
Vinyl acetate (108-05-4)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA ACGIH	ACGIH STEL (ppm)	15 ppm

8.2. Exposure controls

Appropriate engineering controls	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.
Hand protection	: Wear suitable gloves.
Eye protection	: Safety glasses or goggles are recommended when using product.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Environmental exposure controls	: Maintain levels below Community environmental protection thresholds.
Other information	: Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas/Pressurized Liquid.
Appearance	: Clear.
Colour	: White.
Odour	: Sweet.
Odour threshold	: No data available.
pH	: 5.5 - 7.5
Relative evaporation rate (butylacetate=1)	: No data available.
Melting point	: No data available.
Freezing point	: No data available.
Boiling point	: No data available.
Flash point	: No data available.
Self ignition temperature	: No data available.
Decomposition temperature	: No data available.
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available.
Relative vapour density at 20 °C	: > 1 (Air = 1)
Relative density	: 1.03
Solubility	: No data available.
Log Pow	: No data available.
Log Kow	: No data available.
Viscosity, kinematic	: No data available.
Viscosity, dynamic	: No data available.
Explosive properties	: No data available.
Oxidising properties	: No data available.
Explosive limits	: No data available.

9.2. Other information

No additional information available

TAJ Eco Bond LVT

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reaction known under conditions of normal use.

10.2. Chemical stability

Stable under normal storage conditions. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Keep in a cool place.

10.3. Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Oxidizers. Nitrates. Chlorine bleach.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

TAJ Eco Bond LVT	
LD50 oral rat	Not available.
LD50 dermal rabbit	Not available.
LC50 inhalation rat	Not available.

1,1-Difluoroethane (75-37-6)	
LC50 inhalation mouse	977 g/m ³ /2h

Vinyl acetate (108-05-4)	
LD50 oral rat	2920 mg/kg
LD50 dermal rabbit	2320 mg/kg
LC50 inhalation rat	11.4 mg/l/4h

Skin corrosion/irritation : Based on available data, the classification criteria are not met.

Serious eye damage/irritation : Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Based on available data, the classification criteria are not met.

Carcinogenicity : Suspected of causing cancer.

Vinyl acetate (108-05-4)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure) : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure) : Based on available data, the classification criteria are not met.

Aspiration hazard : Based on available data, the classification criteria are not met.

Symptoms/injuries after inhalation : May cause respiratory tract irritation.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Symptoms/injuries after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Symptoms/injuries after ingestion : Not a normal route of exposure.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

TAJ Eco Bond LVT	
Persistence and degradability	Not established.

TAJ Eco Bond LVT

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

12.3. Bioaccumulative potential

TAJ Eco Bond LVT

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: This material must be disposed of in accordance with all local, state, provincial, and federal regulations. Pressurized container: Do not pierce or burn, even after use.
--------------------------------	---

SECTION 14: Transport information

In accordance with DOT

14.1. UN number

UN-No.(DOT)	: UN1950
-------------	----------

14.2. UN proper shipping name

DOT Proper Shipping Name	: Aerosols, non-flammable
Department of Transportation (DOT) Hazard Classes	: 2.2
Hazard labels (DOT)	:



14.3. Additional information

Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Vinyl acetate (108-05-4)

Listed on SARA Section 302 (Specific toxic chemical listings)

Listed on SARA Section 313 (Specific toxic chemical listings)

SARA Section 302 Threshold Planning Quantity (TPQ)	1000
--	------

SARA Section 313 - Emission Reporting	0.1 %
---------------------------------------	-------

15.2. US State regulations

TAJ Eco Bond LVT

State or local regulations	This product contains chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.
----------------------------	---

SECTION 16: Other information

Indication of changes	: None.
Date of issue	: 08/26/2016
Other information	: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

31-SDS-TAJ-EB-LVT
DATE: 08/26/2016
REV: A