

AVIAN

TAJ FLOORING

GLOBAL MANUFACTURING, LOCAL SERVICING

RIGID CORE CLICK

5MM, 6MM, 7MM THICKNESS
INCLUDES 1MM ATTACHED
ACOUSTIC CUSHION

9.56" X 60" PLANKS

i4F DROP-LOCK
INTERLOCKING TECHNOLOGY



made in the usa

COMMERCIAL FLOORING

AVIAN RIGID CORE CLICK

A collection of nature-inspired wood visuals designed to transform both residential and light-commercial spaces into serene sanctuaries of style and sophistication.

This flooring solution is phthalate-free and features a high-density polymer core. Its innovative i4F Drop-Lock interlocking technology simplifies the installation process, making it quicker and easier, while also ensuring water-resistance. The 1MM attached cushioned underlayment enhances comfort underfoot and acoustic performance.

SIZE: 9.56" x 60" PLANKS



TAJ-10120 Gull



TAJ-10121 Chickadee



TAJ-10122 Kingfisher



TAJ-10123 Sparrow



TAJ-10124 Swan



TAJ-10125 Thrush



TAJ-10126 Wren



TAJ-10127 Thrasher



TAJ-10128 Meadowlark



TAJ-10129 Sandpiper



TAJ-10130 Falcon



TAJ-10131 Warbler



TAJ-10132 Robin



TAJ-10133 Hawk



SCAN TO VIEW THE
COLLECTION ON
tajflooring.com

Color and shading of product images to sample may vary. Viewing actual samples is recommended.



FEATURED PRODUCT / TAJ-10121 CHICKADEE



i4F Drop-Lock technology enables
up to 30% faster installation
compared to traditional glue-down
methods, reducing both labor time
and project disruption.



FEATURED PRODUCT / TAJ-10127 THRASHER



FEATURED PRODUCT / TAJ-10129 SANDPIPER

SPECIFICATION OVERVIEW

Construction	High-density polymer core (HDPC) flooring, free from ortho phthalates
Thickness & Wear Layer Options	4MM + 1MM attached acoustic cushion backing, 12MIL wear layer 4MM + 1MM attached acoustic cushion backing, 20MIL wear layer 5MM + 1MM attached acoustic cushion backing, 20MIL wear layer 6MM + 1MM attached acoustic cushion backing, 30MIL wear layer
Finish Coating	UV-cured urethane infused with ceramic particles
Dimensions	Plank: 9.56" x 60"
Edge Treatment	Micro-bevel
Availability	Made-to-order with a 20,000 SF minimum
Installation	Floating, i4F Drop-Lock Interlocking Technology
Warranty	20-Year Limited Light Commercial 30-Year Limited Residential warranty applies to the 5MM + 1MM construction. For warranty terms per additional thicknesses, please contact us.
ASTM E492 Acoustic IIC	57; 7" concrete, no drop ceiling
LEED	May contribute to LEED credits, LEED 2009, IEQ4.3 Low Emitting Materials Flooring



Coordinating accessories available.



Scan to access the full technical specification information including installation and maintenance guides.



phthalate free



sound absorption



made in the USA



interlocking technology



GLOBAL MANUFACTURING, LOCAL SERVICING

(888) 652-2111 | info@tajflooring.com



tajflooring.com